

SNAP SWITCHES



Series Name	Switch Type (Size)	Max UL Current Rating	UL Approved	VDE Approved	Mounting				Degree of Protection	Max. Temp °C	Circuitry				Terminals				Actuator Types				Contact System					
					Threaded Ferrule	Mounting Holes	Snap In				SPDT	DPDT	SPST	Line Interrupt	Quick Connect	PC	Solder	Screw	Wire Leads	Button	Flat Lever	Simulated Roller	Roller	Wiping				
DH	Ultraminiature	0.005-0.5 A 30 V DC								70																		
DG	Subsubminiature	0.05-3 A 125 V AC 30 V DC	■							85																		
DJ	Subsubminiature	0.005-2 A 12 V DC							IP67	85																		
DK	Subsubminiature	0.005-2 A 12 V DC							IP65	85																		
DR	Subsubminiature	0.005-2 A 12 V DC								85																		
DB	Subminiature	0.1-10 A 250 V AC	■	■					IP50	120			■															
DC	Subminiature	0.1-10 A 250 V AC	■	■					IP67	120																		
DZ	Subminiature	3 A 250 V AC	■	■						85																		
DCJK	Subminiature	0.1-10 A 250 V AC							IP67	120																		
D3	Miniature	4-16 A 250 V AC	■	■						85																		
D4	Miniature	0.1-21 A 250 V AC	■	■					IP40	150																		
W4	Miniature	0.1-16 A 250 V AC	■	■					IP40	85																		■
E	General Purpose	0.1-30.1 A 250 V AC	■							150			■															
GP	General Purpose	5 A 125 V AC-25 A 250 V AC	■							85																		
E/F6, E/F7	Panel Mount	0.1-16 A 125/250 V AC	■	■						85			■															
F8	Panel Mount	0.1-16 A 125/250 V AC	■	■						85																		
NM02	Center-Off	0.05-0.1 A 12 V DC							IP67	85																		

